

ACE EQUIPMENT CO.
Cleveland, Ohio

ACE BURN-OFF OVEN FEATURES

MODEL 3455-RT

PHYSICAL

Inside Dimensions W/O Cart	60"W x 156"D x 99"H
Inside Dimensions With Cart	60"W x 156"D x 81"H
Volume Over Cart	439 CU. FT.
Single Platform Cart Dimensions	57"W x 153"D x 18"H
Outside Dimensions	108"W x 188"D x 112"H
Shipping Weight	7,000 LBS.
Location of Controls	Right Side
Location of Exhaust Stack	Top Rear Left Corner
Exhaust Stack Included	16"ID x 20"OD x 10' L

FUEL

Max. Primary Burner 1 Input	150,000 BTU/HR
Max Primary Burner 2 Input	150,000 BTU/HR
Max Afterburner Input	650,000 BTU/HR
Avg Prim & After. Total Hi-Lo Input	
Natural Gas Inlet Pressure	8" to 14" W.C.
Propane Inlet Pressure	12" to 18" W.C.
Gas Inlet Pipe Size	1-1/2"

ELECTRIC

Voltage/Phase/Hertz	120/1/60
Amps	* 5 to 10

WATER

Normal Capacity	Less Than 3.6 Gal/HR.
Min/Max Pressure	6 Gal./HR. Ea. Nozzle 30 to 60 PSI

CYCLE TIME/CAPACITY

* Normal Cycle Time	2 to 8 Hours
* Combustible Capacity	60 LBS/HR

* Varies with the combustible load and oven size.

CONTROLS

Primary Burner - Normal	800°F (427°C)
Afterburner - Before Primary Ignites	1,500°F (798°C)
Over Temp. Control	Standard
Primary Water Spray	Standard
Secondary Water Spray	Standard
NFPA-86 Specifications	Standard
FM/IRI Specifications	Optional OA-2600
U.L. Listed Control Panel	Standard
ISO Control Certified	Standard
Primary Burner off on Loss of A.B.	Standard
Primary & A.B. Burners Rated For Automatic Shutoff System	800,000 BTU/HR Standard
One Touch Control (OTC) System	Optional OA-100
High Fire Afterburner 1,500°F (798°C)	Optional OA-1091

CONSTRUCTION

Cart Rating	8,000 LBS.
Cart 4" Structural Channel	7.25 LBS/FT
Oven Steel Enclosure	11 Ga. CRS
Oven Enclosure Front Face	1/4" CRS Plate
Angle Iron Reinforced Enclosure	Standard
Wall Insulation 3" Thick 2,300°F.	Standard
Top, Floor & Door Insulation 4" Thick	Standard
Aluminized Coating Inside Enclosure	Standard
Steel Floor Covers Over 4" Insulation	3/16" CRS
Exterior Finish Hi-Temp.	Blue Enamel
Exhaust Stack Insulation Rated	2,700°F. 2" Thick
Qty Top Mounted Pressure Relief Hatch	2 Standard
Qty Primary Water Nozzles	6 Standard
Qty Secondary Water Nozzles	8 Standard
Qty Primary Burners	2 Standard
Qty Afterburners	1 Standard

NFPA Preferred Vent Ratio: 1:15

WARRANTY

The oven is warranted to be free from defects in material and workmanship on the date of sale by ACE or an authorized ACE distributor to the original purchaser who states he will use the oven. As purchaser's sole remedy for breach of this warranty, ACE will, for a period of twelve months from the date of sale, repair or replace any part of the equipment which is proven to be defective. This warranty applies only when the oven is installed, operated and maintained in accordance with ACE's recommendations.

This data is based on our standard ovens. Any deviation from our standards, may result in changes to this data.

t:\Marketing\ovens\spec sheets\value added specifications