

COIL WINDING

Model 4C-3000 Tel-A-Tension Tension Controller and Monitor

- High performance tensioning device
- Continuously displays actual tension in grams during the winding cycle
- Includes two interchangeable, calibrated scales
- Self-compensating braking system maintains current tension
- Low inertia assures uniform tension during rapid starts and stops
- Accommodates a greater extent of wire sizes because of its expanded tension ranges
- Precision pointer makes for easy readout
- Easily adaptable for single or multiple winding setups
- Inexpensive wear parts assure a long life
- Calibrated scale #1: 1.2 kilograms, AWG #25 to #32
- Calibrated scale #2: 3.5 kilograms, AWG #20 to #26
- *Heavy duty kit: 7.1 kilograms, AWG #16 to #21
- *Requires Heavy Duty Kit



MODEL 4C-3000 SPECIFICATIONS:			
SIZE	9.75" H X 8" L X 6.5 W		
WEIGHT - HEAD ONLY	2.5 LBS (1.1 KGS.)		
MODEL 4C-3000	TEL-A-TENSION HEAD ONLY	MODEL 4C-3000-P6:	
		SIZE	20" H X 8" L X 6.5"W
MODEL 4C-3000-P6	WITH STAND FOR 6" DIA. SPOOL	WEIGHT-STAND ONLY	2.9 LBS (1.3 KGS.)
		MODEL 4C-3000-P12:	
		SIZE	36.25"H X 16.5L X 14.5 W
MODEL 4C-3000-P12	WITH STAND FOR 12" DIA. SPOOL	WEIGHT- HEAD ONLY	19.6 LBS (8.9 KGS.)

Other Models Available per Wire Size

Model 30-350G (Model 3000) For AWG#31-#44

Model 30-40G (Model 3000F) For AWG#40-#47

Model 30-700G (Model 3000-H) For AWG #28-#40

Model 4C3000 For AWG #16-#32



Wisker Disk

Over 90% of basic de-reeling problems are solved simply by using a wisker disk - regardless of spool size.

L = Light.....35 AWG or finer

H = Heavy....35-25 AWG

XH = Extra Heavy....Heavier than 25AWG

Available custom sizes made to your specifications in sizes from 1.5" to 30"

