

ACE HEAT CLEANING OVENS-RKG Series

MODEL (-RKG)	INSIDE DIMENSIONS						OVER CART		OUTSIDE DIMENSIONS						CART RATING		VOLUME OVER CART		MAX COMBU- STBLE		NATURAL GAS		SHIPPING WEIGHT	
	WIDTH		DEPTH		HEIGHT				WIDTH		DEPTH		HEIGHT											
	N.	M.	N.	M.	N.	M.	N.	M.	N.	M.	N.	M.	N.	M.	LBS	KGS	CF	CM	LBS HR	KGS HR	MAX CFH	MAX CMH	LBS	KGS
230	36	0.91	36	0.91	47	1.19	36	0.91	56	1.42	64	1.63	58	1.47	3,200	1,452	27	0.76	30	14	625	17.69	2,000	907
330	36	0.91	60	1.52	35	0.89	24	0.61	56	1.42	88	2.24	61	1.55	2,000	907	30	0.85	30	14	625	17.69	2,200	998
363	36	0.91	84	2.13	47	1.19	47	1.19	56	1.42	117	2.97	60	1.52	4,500	2,041	63	1.78	35	16	625	17.69	3,500	1,588
463 R	36	0.91	36	0.91	95	2.41	84	2.13	59	1.50	64	1.63	108	2.74	800	363	63	1.78	35	16	625	17.69	3,400	1,542
240	48	1.22	48	1.22	59	1.50	48	1.22	68	1.73	76	1.93	70	1.78	3,200	1,452	64	1.81	40	18	625	17.69	2,300	1,043
472 R	36	0.91	48	1.22	83	2.11	72	1.83	56	1.42	76	1.93	96	2.44	800	363	72	2.04	40	18	625	17.69	3,500	1,588
490 R	36	0.91	48	1.22	101	2.57	90	2.29	56	1.42	78	1.98	114	2.90	800	363	90	2.55	40	18	625	17.69	3,700	1,678
496 R	48	1.22	48	1.22	83	2.11	72	1.83	71	1.80	78	1.98	96	2.44	800	363	96	2.72	40	18	625	17.69	3,700	1,678
4112 R	48	1.22	48	1.22	95	2.41	84	2.13	71	1.80	78	1.98	108	2.74	800	363	112	3.17	40	18	625	17.69	3,800	1,724
3120	48	1.22	60	1.52	84	2.13	72	1.83	71	1.80	97	2.46	97	2.46	8,000	3,629	120	3.40	50	23	625	17.69	3,950	1,792
245	60	1.52	60	1.52	72	1.83	60	1.52	80	2.03	94	2.39	85	2.16	8,000	3,629	125	3.54	50	23	625	17.69	4,000	1,814
4128 R	48	1.22	48	1.22	107	2.72	96	2.44	71	1.80	78	1.98	120	3.05	800	363	128	3.62	40	18	635	17.69	4,100	1,860
3144	48	1.22	108	2.74	60	1.52	48	1.22	66	1.68	143	3.63	73	1.85	4,800	2,177	144	4.08	40	18	625	17.69	4,000	1,814
4150 R	48	1.22	48	1.22	123	3.12	112	2.84	71	1.80	78	1.98	136	3.45	800	363	150	4.23	40	18	625	17.69	4,300	1,950
3160	48	1.22	120	3.05	60	1.52	48	1.22	66	1.68	155	3.94	73	1.85	5,000	2,268	160	4.53	40	18	625	17.69	4,300	1,950
3168	48	1.22	84	2.13	86	2.18	72	1.83	71	1.80	119	3.02	99	2.51	8,000	3,629	168	4.76	40	18	625	17.69	4,350	1,973
3175	60	1.52	60	1.52	96	2.44	84	2.13	80	2.03	94	2.39	109	2.76	8,000	3,629	175	4.95	50	23	625	17.69	4,400	1,996
3189	36	0.91	252	6.40	48	1.22	36	0.91	80	2.03	270	6.86	61	1.55	5,000	2,268	189	5.35	40	18	1,200	33.96	6,000	2,722
3210	72	1.83	84	2.13	72	1.83	60	1.52	100	2.54	120	3.05	104	2.64	8,000	3,629	210	5.94	60	27	625	17.69	4,700	2,132
260	72	1.83	72	1.83	83	2.11	72	1.83	100	2.54	110	2.79	99	2.51	8,000	3,629	216	6.11	60	27	625	17.69	5,000	2,268
3245	84	2.13	84	2.13	75	1.91	60	1.52	106	2.69	120	3.05	104	2.64	8,000	3,629	245	6.93	60	27	850	24.01	5,700	2,586
3288	72	1.83	96	2.44	86	2.18	72	1.83	100	2.54	135	3.43	99	2.51	8,000	3,629	288	8.15	60	27	850	24.01	6,000	2,722
4288	72	1.83	72	1.83	110	2.79	96	2.44	100	2.54	112	2.84	123	3.12	8,000	3,629	288	8.15	60	27	850	24.01	6,500	2,722
3336	72	1.83	96	2.44	99	2.52	84	2.13	100	2.54	143	3.63	112	2.85	8,000	3,629	336	9.50	65	30	950	26.88	7,000	3,175
270	84	2.13	84	2.13	99	2.52	84	2.13	109	2.77	124	3.15	112	2.85	8,000	3,629	343	9.71	70	32	1,000	28.30	7,000	3,175
3375	60	1.52	180	4.57	72	1.83	60	1.52	108	2.74	212	5.39	85	2.16	8,000	3,629	375	10.61	70	32	1,000	28.30	7,500	3,402
3416	96	2.44	96	2.44	93	2.36	78	1.98	125	3.18	143	3.63	106	2.69	8,000	3,629	416	11.77	70	32	1,100	31.13	8,000	3,629
3432	72	1.83	216	5.49	63	1.60	48	1.22	126	3.20	255	6.48	77	1.96	8000	3629	432	12.23	70	32	1,200	33.96	7,500	3,402
3455	60	1.52	156	3.96	99	2.52	84	2.13	108	2.74	188	4.78	112	2.85	8,000	3,629	455	12.88	60	29	1,000	28.30	7,000	3,175
280	96	2.44	96	2.44	105	2.67	90	2.29	121	3.07	140	3.56	120	3.05	8,000	3,629	480	13.58	80	36	1,100	31.13	8,900	4,037
3512	96	2.44	96	2.44	111	2.82	96	2.44	121	3.07	140	3.56	124	3.15	8,000	3,629	512	14.49	80	36	1,100	31.13	9,200	4,173
3600	96	2.44	120	3.05	105	2.67	90	2.29	121	3.07	162	4.11	118	3.00	8,000	3,629	600	16.98	80	36	1,400	39.62	9,500	4,309
3704	96	2.44	132	3.35	111	2.82	96	2.44	121	3.07	174	4.41	124	3.15	8,000	3,629	704	19.94	80	36	1,500	42.48	11,050	4,999

NATURAL GAS INLET PRESSURE 8" TO 14" WATER COLUMN (20 cm to 30 cm W.C.)

PROPANE INLET PRESSURE 12" TO 18" WATER COLUMN (30 cm to 46 cm W.C.)

R = HANGING RACK WITH CART STANDARD (HIGH BOY MODELS)

MAX. AMP = 10

POWER SUPPLY AMP 120/1/50/60

MAXIMUM CONTINUOUS DUTY OPERATING TEMP.: 900°F (482°C)

MAXIMUM INTERMITTENT DUTY OPERATING TEMP.: 1000°F (538°C)

WATER PRESSURE MINIMUM: 30 PSI

WATER PRESSURE MAXIMUM: 50 PSI

(OVER 50 PSI REQUIRES REGULATOR)



ACE HEAT CLEANING OVENS-RT Series

MODEL (-RT-)	INSIDE DIMENSIONS						OVER CART		OUTSIDE DIMENSIONS						CART RATING		VOLUME OVER CART		MAX COMBU-STIBLE		NATURAL GAS		SHIPPING WEIGHT	
	WIDTH		DEPTH		HEIGHT		IN.	M.	IN.	M.	IN.	M.	IN.	M.	LBS	KGS	C F	C M	LBS HR	KGS HR	MAX CFH	MAX CMH	LBS	KGS
	IN.	M.	IN.	M.	IN.	M.																		
230	36	0.91	36	0.91	47	1.19	33	0.84	56	1.42	64	1.63	58	1.47	3,200	1,452	25	0.71	30	14	625	17.69	2,000	907
330	36	0.91	60	1.52	35	0.89	21	0.53	56	1.42	88	2.24	61	1.55	2,000	907	26	0.74	30	14	625	17.69	2,200	998
363	36	0.91	84	2.13	47	1.19	33	0.84	56	1.42	117	2.97	60	1.52	4,500	2,041	58	1.64	35	16	625	17.69	3,500	1,588
463 R	36	0.91	36	0.91	95	2.41	81	2.06	59	1.50	64	1.63	108	2.74	800	363	61	1.73	35	16	625	17.69	3,400	1,542
240	48	1.22	48	1.22	59	1.50	45	1.14	68	1.73	76	1.93	70	1.78	3,200	1,452	60	1.70	40	18	625	17.69	2,300	1,043
472 R	36	0.91	48	1.22	83	2.11	69	1.75	56	1.42	76	1.93	96	2.44	800	363	69	1.95	40	18	625	17.69	3,500	1,588
490 R	36	0.91	48	1.22	101	2.57	87	2.21	56	1.42	78	1.98	114	2.90	800	363	87	2.46	40	18	625	17.69	3,700	1,678
496 R	48	1.22	48	1.22	83	2.11	69	1.75	71	1.80	78	1.98	96	2.44	800	363	92	2.60	40	18	625	17.69	3,700	1,678
4112 R	48	1.22	48	1.22	95	2.41	81	2.06	71	1.80	78	1.98	108	2.74	800	363	108	3.06	40	18	625	17.69	3,800	1,724
3120	48	1.22	60	1.52	84	2.13	69	1.75	71	1.80	97	2.46	97	2.46	8,000	3,629	115	3.25	50	23	625	17.69	3,950	1,792
245	60	1.52	60	1.52	72	1.83	57	1.45	80	2.03	94	2.39	85	2.16	8,000	3,629	119	3.37	50	23	625	17.69	4,000	1,814
4128 R	48	1.22	48	1.22	107	2.72	93	2.36	71	1.80	78	1.98	120	3.05	800	363	124	3.51	40	18	635	17.69	4,100	1,860
3144	48	1.22	108	2.74	60	1.52	45	1.14	66	1.68	143	3.63	73	1.85	4,800	2,177	135	3.82	40	18	625	17.69	4,000	1,814
4150 R	48	1.22	48	1.22	123	3.12	109	2.77	71	1.80	78	1.98	136	3.45	800	363	145	4.10	40	18	625	17.69	4,300	1,950
3160	48	1.22	120	3.05	60	1.52	45	1.14	66	1.68	155	3.94	73	1.85	5,000	2,268	150	4.25	40	18	625	17.69	4,300	1,950
3168	48	1.22	84	2.13	86	2.18	69	1.75	71	1.80	119	3.02	99	2.51	8,000	3,629	161	4.56	40	18	625	17.69	4,350	1,973
3175	60	1.52	60	1.52	96	2.44	81	2.06	80	2.03	94	2.39	109	2.76	8,000	3,629	169	4.78	50	23	625	17.69	4,400	1,996
3189	36	0.91	252	6.40	48	1.22	33	0.84	80	2.03	270	6.86	61	1.55	5,000	2,268	173	4.90	40	18	1,200	33.96	6,000	2,722
3210	72	1.83	84	2.13	72	1.83	57	1.45	100	2.54	120	3.05	104	2.64	8,000	3,629	200	5.66	60	27	625	17.69	4,700	2,132
260	72	1.83	72	1.83	83	2.11	69	1.75	100	2.54	110	2.79	99	2.51	8,000	3,629	207	5.86	60	27	625	17.69	5,000	2,268
3245	84	2.13	84	2.13	75	1.91	57	1.45	106	2.69	120	3.05	104	2.64	8,000	3,629	233	6.59	60	27	850	24.01	5,700	2,586
3288	72	1.83	96	2.44	86	2.18	69	1.75	100	2.54	135	3.43	99	2.51	8,000	3,629	276	7.81	60	27	850	24.01	6,000	2,722
4288	72	1.83	72	1.83	110	2.79	93	2.36	100	2.54	112	2.84	123	3.12	8,000	3,629	279	7.90	60	27	850	24.01	6,500	2,722
3336	72	1.83	96	2.44	99	2.52	81	2.06	100	2.54	143	3.63	112	2.85	8,000	3,629	324	9.17	65	30	950	26.88	7,000	3,175
270	84	2.13	84	2.13	99	2.52	81	2.06	109	2.77	124	3.15	112	2.85	8,000	3,629	331	9.37	70	32	1,000	28.30	7,000	3,175
3375	60	1.52	180	4.57	72	1.83	57	1.45	108	2.74	212	5.39	85	2.16	8,000	3,629	356	10.08	70	32	1,000	28.30	7,500	3,402
3416	96	2.44	96	2.44	93	2.36	75	1.91	125	3.18	143	3.63	106	2.69	8,000	3,629	400	11.32	70	32	1,100	31.13	8,000	3,629
3432	72	1.83	216	5.49	63	1.60	45	1.14	126	3.20	255	6.48	77	1.96	8000	3629	405	11.46	70	32	1,200	33.96	7,500	3,402
3455	60	1.52	156	3.96	99	2.52	81	2.06	108	2.74	188	4.78	112	2.85	8,000	3,629	439	12.42	60	29	1,000	28.30	7,000	3,175
280	96	2.44	96	2.44	105	2.67	87	2.21	121	3.07	140	3.56	120	3.05	8,000	3,629	464	13.13	80	36	1,100	31.13	8,900	4,037
3512	96	2.44	96	2.44	111	2.82	93	2.36	121	3.07	140	3.56	124	3.15	8,000	3,629	496	14.04	80	36	1,100	31.13	9,200	4,173
3600	96	2.44	120	3.05	105	2.67	87	2.21	121	3.07	162	4.11	118	3.00	8,000	3,629	580	16.41	80	36	1,400	39.62	9,500	4,309
3704	96	2.44	132	3.35	111	2.82	93	2.36	121	3.07	174	4.41	124	3.15	8,000	3,629	682	19.30	80	36	1,500	42.48	11,050	4,999
31453	120	3.05	192	4.88	125	3.18	108	2.74	174	4.42	236	5.99	143	3.63	8,000	3,629	1440	40.78	100	45	3,700	104.77	30,000	13,636